



# MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI and Canadian WHMIS Standards

## 1. PRODUCT IDENTIFICATION

**CHEMICAL NAME; CLASS:** NON-FLAMMABLE GAS MIXTURE  
**Containing One or More of the Following Components in a Nitrogen Balance Gas:**  
**Oxygen 0-23.5%; Ethanol, 0.0005-2.0%**

**SYNONYMS:** Not Applicable

**CHEMICAL FAMILY NAME:** Not Applicable

**FORMULA:** Not Applicable

**Document Number:** 50032

**Note:** The Material Safety Data Sheet is for this gas mixture supplied in cylinders with 33 cubic feet (935 liters) or less gas capacity (DOT - 39 cylinders). This MSDS has been developed for various gas mixtures with the composition of components within the ranges listed in Section 2 (Composition and Information on Ingredients). Refer to the product label for information on the actual composition of the product.

<b>PRODUCT USE:</b>	Calibration of Monitoring and Research Equipment
<b>SUPPLIER/MANUFACTURER'S NAME:</b>	CALGAZ
<b>ADDRESS:</b>	821 Chesapeake Drive Cambridge, MD 21613
<b>EMERGENCY PHONE:</b>	CHEMTREC: 1-800-424-9300
<b>BUSINESS PHONE:</b>	1-410-228-6400
	General MSDS Information 1-713/868-0440
	Fax on Demand: 1-800/231-1366

## 2. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	mole %	EXPOSURE LIMITS IN AIR					
			ACGIH-TLV		OSHA-PEL		NIOSH IDLH	OTHER
			TWA ppm	STEL ppm	TWA ppm	STEL ppm		
Ethanol	61-17-5	0.0005-2.0%	1000	NE	1000	NE	3300	NIOSH REL: TWA = 1000 DFG MAKs: TWA = 1000 PEAK = 2•MAK, 15 min. average value, 1 hr interval Carcinogen: MAK-5, TLV-A4
Oxygen	7782-44-7	0-23.5%	There are no specific exposure limits for Oxygen. Oxygen levels should be maintained above 19.5%.					
Nitrogen	7727-37-9	Balance	There are no specific exposure limits for Nitrogen. Nitrogen is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.					

NE = Not Established.

See Section 16 for Definitions of Terms Used.

NOTE : All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1998 format.

## 3. HAZARD IDENTIFICATION

**EMERGENCY OVERVIEW:** This gas mixture is a colorless gas which is odorless, or which has a slight, alcohol-like odor. Releases of this gas mixture may produce oxygen-deficient atmospheres (especially in confined spaces or other poorly-ventilated environments); individuals in such atmospheres may be asphyxiated. Inhalation of Ethanol, a component of this gas mixture, may cause drowsiness and other central nervous system effects at concentrations above 1000 ppm (0.1%).

**SYMPTOMS OF OVER-EXPOSURE BY ROUTE OF EXPOSURE:** The most significant route of over-exposure for this gas mixture is by inhalation.

**INHALATION:** Due to the small size of an individual cylinder of this gas mixture, no unusual health effects from over-exposure to the product are anticipated under routine circumstances of use. The chief health hazard associated with this gas mixture is when this gas mixture contains less than 19.5% Oxygen and is released in a small, poorly-ventilated area (i.e. an enclosed or confined space). Under this circumstance, an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The effects associated with various levels of oxygen are as follows:

### CONCENTRATION OF OXYGEN

12-16% Oxygen:

10-14% Oxygen:

6-10% Oxygen:

Below 6%:

### OBSERVED EFFECT

Breathing and pulse rate increased, muscular coordination slightly disturbed.

Emotional upset, abnormal fatigue, disturbed respiration.

Nausea, vomiting, collapse, or loss of consciousness.

Convulsive movements, possible respiratory collapse, and death.

Additionally, there is a potential for over-exposure to Ethanol vapors. Inhalation of concentrations below 1,000 ppm (0.1%) of Ethanol usually produces no signs of intoxication. Exposure to concentrations over 1,000 ppm may cause headache, irritation of the eyes, nose, and throat, and, if continued for an hour, drowsiness and lassitude, loss of appetite, and inability to concentrate. Currently, there is no concrete evidence that repeated exposure to ethanol vapor results in cirrhosis of the liver.

**HEALTH EFFECTS OR RISKS FROM EXPOSURE: An Explanation in Lay Terms.** Over-exposure to this gas mixture may cause the following health effects:

**ACUTE:** Due to the small size of the individual cylinder of this gas mixture, no unusual health effects from exposure to the product are anticipated under routine circumstances of use. The most significant hazard associated with this gas mixture when it contains less than 19.5% oxygen is the potential for exposure to oxygen-deficient atmospheres. Symptoms of oxygen deficiency include respiratory difficulty, ringing in ears, headaches, shortness of breath, wheezing, headache, dizziness, indigestion, nausea, unconsciousness, and death. The skin of a victim of over-exposure may have a blue color.

**CHRONIC:** Chronic exposure to oxygen-deficient atmospheres (below 18% oxygen in air) may affect the heart and nervous system.

**TARGET ORGANS:** ACUTE: Respiratory system, central nervous system. CHRONIC: Heart, central nervous system.

## 4. FIRST-AID MEASURES

**RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO THIS PRODUCT WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus must be worn.**

No unusual health effects are anticipated after exposure to this gas mixture, due to the small cylinder size. If any adverse symptom develops after over-exposure to this gas mixture, remove victim(s) to fresh air as quickly as possible. Only trained personnel should administer supplemental oxygen and/or cardio-pulmonary resuscitation if necessary. Victim(s) who experience any adverse effect after over-exposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

#### 4. FIRST-AID MEASURES (Continued)

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Acute or chronic respiratory conditions may be aggravated by over-exposure to the components of this gas mixture.

**RECOMMENDATIONS TO PHYSICIANS:** Administer oxygen, if necessary; treat symptoms; eliminate exposure.

#### 5. FIRE-FIGHTING MEASURES

**FLASH POINT:** Not applicable.

**AUTOIGNITION TEMPERATURE:** Not applicable.

**FLAMMABLE LIMITS (in air by volume, %):**

Lower (LEL): Not applicable.

Upper (UEL): Not applicable.

**FIRE EXTINGUISHING MATERIALS:** Non-flammable gas mixture. Use extinguishing media appropriate for surrounding fire.


**UNUSUAL FIRE AND EXPLOSION HAZARDS:** This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.

Explosion Sensitivity to Mechanical Impact: Not sensitive.

Explosion Sensitivity to Static Discharge: Not sensitive.

**SPECIAL FIRE-FIGHTING PROCEDURES:** Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment.

#### NFPA RATING



#### 6. ACCIDENTAL RELEASE MEASURES

**LEAK RESPONSE:** Due to the small size and content of the cylinder, an accidental release of this gas mixture presents significantly less risk of an oxygen deficient environment and other safety hazards than a similar release from a larger cylinder. However, as with any chemical release, extreme caution must be used during emergency response procedures. In the event of a release in which the atmosphere is unknown, and in which other chemicals are potentially involved, evacuate immediate area. Such releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a leak, clear the affected area, protect people, and respond with trained personnel. Allow the gas mixture to dissipate. If necessary, monitor the surrounding area (and the original area of the release) for oxygen. Oxygen levels must be above 19.5% before non-emergency personnel are allowed to re-enter area.

If leaking incidentally from the cylinder, contact your supplier.

#### 7. HANDLING and USE

**WORK PRACTICES AND HYGIENE PRACTICES:** Be observant for the odor of sulfur; this odor is indicative of a potential over-exposure the Sulfur Dioxide of this gas mixture. Do not attempt to repair, adjust, or in any other way modify cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact the nearest distributor immediately. Eye wash stations/safety showers should be near areas where this gas mixture is used or stored. All work operations should be monitored in such a way that emergency personnel can be immediately contacted in the event of a release. All work practices should minimize releases of Sulfur Dioxide and Nitrogen Monoxide-containing gas mixtures.

**STORAGE AND HANDLING PRACTICES:** Cylinders should be firmly secured to prevent falling or being knocked-over. Cylinders must be protected from the environment, and preferably kept at room temperature (approximately 21°C [70°F]). Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a first-in, first-out inventory system to prevent full containers from being stored for long periods of time. These cylinders are not refillable. **WARNING! Do not refill DOT 39 cylinders. To do so may cause personal injury or property damage.**

**SPECIAL PRECAUTIONS FOR HANDLING GAS CYLINDERS:** **WARNING!** Compressed gases can present significant safety hazards. During cylinder use, use equipment designed for these specific cylinders. Ensure all lines and equipment are rated for proper service pressure.

**PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely. Always use product in areas where adequate ventilation is provided.

#### 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

**VENTILATION AND ENGINEERING CONTROLS:** No special ventilation systems or engineering controls are needed under normal circumstances of use. As with all chemicals, use this gas mixture in well-ventilated areas. If this gas mixture is used in a poorly-ventilated area, install automatic monitoring equipment to detect the levels of Ethanol and Oxygen.

**RESPIRATORY PROTECTION:** No special respiratory protection is required under normal circumstances of use. Maintain Ethanol levels below 50% of the TLV (TLV = 1000 ppm) and oxygen levels above 19.5% in the workplace. Use supplied air respiratory protection when Ethanol levels exceed 50% of the TLV (TLV = 1000 ppm), oxygen levels are below 19.5%, or during emergency response to a release of this gas mixture. During an emergency situation, before entering the area, check the concentration of Ethanol and Oxygen. If respiratory protection is required, follow the requirements of the Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), or equivalent State standards.

**EYE PROTECTION:** Safety glasses. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

**HAND PROTECTION:** Wear leather gloves when handling cylinders. Chemically resistant gloves should be worn when using this gas mixture. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

**BODY PROTECTION:** No special protection is needed under normal circumstances of use. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

#### 9. PHYSICAL and CHEMICAL PROPERTIES

The following information is for Nitrogen, the main component of this gas mixture.

**GAS DENSITY @ 32°F (0°C) and 1 atm:** .072 lbs/ ft<sup>3</sup> (1.153 kg/m<sup>3</sup>)

**FREEZING/MELTING POINT @ 10 psig:** -345.8°F (-210°C)

**SPECIFIC GRAVITY (air = 1) @ 70°F (21.1°C):** 0.906

**SOLUBILITY IN WATER vol/vol @ 32°F (0°C) and 1 atm:** 0.023

**EVAPORATION RATE (nBuAc = 1):** Not applicable.

**VAPOR PRESSURE @ 70°F (21.1°C) (psig):** Not applicable.

**COEFFICIENT WATER/OIL DISTRIBUTION:** Not applicable.

**BOILING POINT:** -320.4°F (-195.8°C)

**pH:** Not applicable.

**MOLECULAR WEIGHT:** 28.01

**EXPANSION RATIO:** Not applicable.

**SPECIFIC VOLUME (ft<sup>3</sup>/lb):** 13.8

The following information is for this gas mixture.

**APPEARANCE AND COLOR:** This gas mixture is a colorless gas which is odorless, or which has a slight, alcohol-like odor.

**HOW TO DETECT THIS SUBSTANCE (warning properties):** The odor may act as a warning property associated with a release of this gas mixture. In terms of leak detection, fittings and joints can be painted with a soap solution to detect leaks, which will be indicated by a bubble formation.

#### 10. STABILITY and REACTIVITY

**STABILITY:** Normally stable in gaseous state.

**DECOMPOSITION PRODUCTS:** The thermal decomposition products of Ethanol in air include carbon oxides. The other components of this gas mixture do not decompose, per se, but can react with other compounds in the heat of a fire.

**MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:** Titanium will burn in Nitrogen (the main component of this gas mixture). Lithium reacts slowly with Nitrogen at ambient temperatures. Components of this gas mixture (Ethanol) are also incompatible with strong oxidizers (i.e. chlorine, bromine pentafluoride, oxygen difluoride, and nitrogen trifluoride).

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Contact with incompatible materials. Cylinders exposed to high temperatures or direct flame can rupture or burst.

## 11. TOXICOLOGICAL INFORMATION

**TOXICITY DATA:** The following toxicology data are available for the components of this gas mixture:

### ETHANOL:

Open Irritation Test (Skin-Rabbit) 400 mg: Mild  
Standard Draize Test (Skin-Rabbit) 20 mg/24 hours: Moderate  
Standard Draize Test (Eye-Rabbit) 500 mg: Severe  
Standard Draize Test (Eye-Rabbit) 500 mg/24 hours: Mild  
Rinsed with Water (Eye-Rabbit): 100 mg/4 seconds: Moderate  
TDLo (Oral-Infant) 11712 µL/kg: Behavioral: general anesthetic; Cardiac: arrhythmias (including changes in conduction); Lungs, Thorax, or Respiration: dyspnea  
TDLo (Oral-Woman) 1200 mg/kg/3 hours: Endocrine: changes in gonadotropins, other changes; Blood: other changes  
TDLo (Oral-Woman) 256 mg/kg/12 weeks: Behavioral: hallucinations, distorted perceptions; Endocrine: effect on menstrual cycle

### ETHANOL (continued):

TDLo (Oral-Man) 22,500 mg/kg/4 weeks-intermittent: Endocrine: other changes; Blood: other changes  
TDLo (Oral-Man) 3371 µL/kg: Behavioral: altered sleep time (including change in righting reflex); Behavioral: excitement, coma  
TDLo (Oral-Man) 700 mg/kg: Behavioral: changes in psychophysiological tests  
TDLo (Oral-Man) 50 mg/kg: Gastrointestinal: alteration in gastric secretion; Gastrointestinal: other changes  
TDLo (Oral-Man) 1430 µg/kg: Behavioral: changes in motor activity (specific assay), ataxia, antipsychotic  
TDLo (Oral-Child) 14400 mg/kg/30 minutes-intermittent: Behavioral: coma; Lungs, Thorax, or Respiration: dyspnea; Gastrointestinal: nausea or vomiting

### ETHANOL (continued):

LDLo (Oral-Child) 2 gm/kg: Lungs, Thorax, or Respiration: other changes; Liver: fatty liver degeneration; Blood: other changes  
LDLo (Oral-Human) 1400 mg/kg: Behavioral: sleep, headache; Gastrointestinal: nausea or vomiting  
LDLo (Oral-Infant) 19,440 mg/kg: Behavioral: convulsions or effect on seizure threshold, coma; Nutritional and Gross Metabolic: body temperature decrease  
LD<sub>50</sub> (Oral-Rat) 7060 mg/kg: Lungs, Thorax, or Respiration: other changes  
LC<sub>50</sub> (Inhalation-Rat) 20,000 ppm/10 hours  
**NITROGEN:** There are no specific toxicology data for Nitrogen. Nitrogen is a simple asphyxiant, which acts to displace oxygen in the environment.

**SUSPECTED CANCER AGENT:** The components of this gas mixture are listed by agencies tracking the carcinogenic potential of chemical compounds, as follows:

**ETHANOL:** ACGIH TLV-A4 (Not Suspected as a Human Carcinogen-the agent is not suspected to be a human carcinogen on the basis of properly conducted epidemiologic studies in humans); MAK-5 (Substances With Carcinogenic and Genotoxic Effects, the Potency of Which is Considered to Be So Low that, provided the MAK and BAT values are observed, no significant contribution to cancer risk is to be expected.)

The remaining components of this gas mixture are not found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, and IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

**IRRITANCY OF PRODUCT:** Contact with rapidly expanding gases can be irritating to exposed skin and eyes.

**SENSITIZATION TO THE PRODUCT:** This gas mixture is not known to cause sensitization in humans; however, some animal studies indicate that exposure to Butane, a component of this gas mixture, can cause weak cardiac sensitization.

**REPRODUCTIVE TOXICITY INFORMATION:** Listed below is information concerning the effects of this gas mixture and its components on the human reproductive system.

**Mutagenicity:** No mutagenicity effects have been described for the components of this gas mixture.

**Embryotoxicity:** No embryotoxic effects have been described for the components of this gas mixture.

**Teratogenicity:** No teratogenicity effects have been described for the components of this gas mixture. Human teratogenic effects are reported for Ethanol, when alcoholic beverages are consumed during pregnancy; however, this type of exposure is not pertinent to this gas mixture,

**Reproductive Toxicity:** No reproductive toxicity effects have been described for the components of this gas mixture.

A **mutagen** is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generation lines. An **embryotoxin** is a chemical which causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A **teratogen** is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A **reproductive toxin** is any substance which interferes in any way with the reproductive process.

**BIOLOGICAL EXPOSURE INDICES (BEIs):** Currently, Biological Exposure Indices (BEIs) have not been determined for the components of this gas mixture.

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL STABILITY:** The components of this gas mixture occur naturally in the atmosphere. The gas will be dissipated rapidly in well-ventilated areas. The following environmental data are applicable to the components of this gas mixture.

### ETHANOL:

Log K<sub>ow</sub> = 0.31; Water Solubility = 100% in water; BOD = 37%-86%/ 5 days (theoretical). This compound occurs naturally in the environment.

Bioconcentration: The low octanol/water partition coefficient indicates that Ethanol will not bioconcentrate in fish.

Aquatic Fate: When released into water, ethanol will volatilize (estimated half life is 6 days) and biodegrade. It will not sorb to sediment or bioconcentrate in aquatic organisms. Although it readily biodegrades in laboratory tests, no data on its rate of degradation in natural waters could be found.

Atmospheric Fate: When released into the atmosphere, ethanol will photodegrade with a half-life ranging from hours in polluted urban atmospheres to approximately 6 days in cleaner atmospheres (based on a hydroxyl radical concentration of 8X10+6 moles/cu cm). Due to its solubility in water, rainout may be an important process.

Terrestrial Fate: When spilled on soil, Ethanol will both evaporate and leach into the ground due to the relatively high vapor pressure and low adsorption in soil. Ethanol will biodegrade in soil, probably to acetic acid and formaldehyde. If degradation is not rapid, it will leach into groundwater.

**NITROGEN:** Water Solubility = 2.4 volumes Nitrogen/100 volumes water at 0°C. 1.6 volumes Nitrogen/100 volumes water at 20°C.

**OXYGEN:** Water Solubility = 1 volume Oxygen/32 volumes water at 20°C. Log K<sub>ow</sub> = -0.65

**EFFECT OF MATERIAL ON PLANTS or ANIMALS:** No evidence is currently available on this gas mixture's effects on plant and animal life.

**EFFECT OF CHEMICAL ON AQUATIC LIFE:** No evidence is currently available on this gas mixture's effects on aquatic life. The following aquatic toxicity data are available for the components of this gas mixture.

### ETHANOL:

LC<sub>50</sub> (*Palaemonetes pugio*, grass shrimp) = 250 mg/L/96 hour  
LC<sub>50</sub> (*Salmo gairdnerii*, rainbow trout) = 13000 mg/L/96 hour  
LC<sub>50</sub> (*Pimephales promelas*, fathead minnow) = 15.3 mg/L/96 hour  
EC<sub>50</sub> (*Pimephales promelas*, fathead minnow) = 12.9 mg/L/96 hour  
LC<sub>50</sub> (*Pimephales promelas*, fathead minnow) = 14.2 mg/L/96 hour

### ETHANOL (Continued):

Cell Multiplication Inhibition Test:  
*Microcystis aeruginosa*, algae = 1450 mg/L  
*Scenedesmus quadricauda*, green algae = 5000 mg/L  
*Entosiphon sulcatum*, protozoa = 65 mg/L  
*Uronema parduczi*, protozoa = 6120 mg/L  
*Pseudomonas putida*, bacteria = 6500 mg/L

## 13. DISPOSAL CONSIDERATIONS

**PREPARING WASTES FOR DISPOSAL:** Waste disposal must be in accordance with appropriate Federal, State, and local regulations. Cylinders with undesired residual product may be safely vented outdoors with the proper regulator. For further information, refer to Section 16 (Other information).

## 14. TRANSPORTATION INFORMATION

**THIS GAS MIXTURE IS HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.**

**PROPER SHIPPING NAME:** Compressed gases, n.o.s. (\*Oxygen, Nitrogen)\*or the gas component with the next highest concentration next to Nitrogen.

**HAZARD CLASS NUMBER and DESCRIPTION:** 2.2 (Non-Flammable Gas)

**UN IDENTIFICATION NUMBER:** UN 1956

**PACKING GROUP:** Not applicable.

**DOT LABEL(S) REQUIRED:** Non-Flammable Gas

**NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000):** 126

**MARINE POLLUTANT:** The components of this gas mixture are not classified by the DOT as Marine Pollutants (as defined by 49 CFR 172.101, Appendix B).

**SPECIAL SHIPPING INFORMATION:** Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

**Note:** DOT 39 Cylinders ship in a strong outer carton (overpack). Pertinent shipping information goes on the outside of the overpack. DOT 39 Cylinders do not have transportation information on the cylinder itself.



## 14. TRANSPORTATION INFORMATION (Continued)

**TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:** This gas is considered as Dangerous Goods, per regulations of Transport Canada.

**PROPER SHIPPING NAME:** Compressed gases, n.o.s. (\*Oxygen, Nitrogen)\* or the gas component with the next highest concentration next to Nitrogen.

**HAZARD CLASS NUMBER and DESCRIPTION:** 2.2 (Non-Flammable Gas)

**UN IDENTIFICATION NUMBER:** UN 1956

**PACKING GROUP:** Not Applicable

**HAZARD LABEL:** Class 2.2 (Non-Flammable Gas)

**SPECIAL PROVISIONS:** None

**EXPLOSIVE LIMIT AND LIMITED QUANTITY INDEX:** 0.12

**ERAP INDEX:** None

**PASSENGER CARRYING SHIP INDEX:** None

**PASSENGER CARRYING ROAD VEHICLE OR PASSENGER CARRYING RAILWAY VEHICLE INDEX:** 75

**NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000):** 121

**NOTE:** Shipment of compressed gas cylinders via Public Passenger Road Vehicle is a violation of Canadian law (Transport Canada Transportation of Dangerous Goods Act, 1992).

## 15. REGULATORY INFORMATION

### ADDITIONAL U.S. REGULATIONS:

**U.S. SARA REPORTING REQUIREMENTS:** The components of this gas mixture is are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

**U.S. SARA THRESHOLD PLANNING QUANTITY:** There are no specific Threshold Planning Quantities for this gas. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

**U.S. TSCA INVENTORY STATUS:** The components of this gas mixture are listed on the TSCA Inventory.

**U.S. CERCLA REPORTABLE QUANTITY (RQ):** Not applicable.

### OTHER U.S. FEDERAL REGULATIONS:

- Ethanol is subject to the requirements of CFR 29 1910.1000 (under the 1989 PELs). Ethanol is listed on Table Z.1.
- No component of this gas mixture is not subject to the reporting requirements of Section 112(r) of the Clean Air Act.
- The regulations of the Process Safety Management of Highly Hazardous Chemicals (29 CFR 1910.119) are not applicable to this gas mixture.
- This gas mixture does not contain any Class I or Class II ozone depleting chemicals (40 CFR Part 82).
- Nitrogen, Oxygen, and Ethanol are not listed as Regulated Substances, per 40 CFR, Part 68, of the Risk Management for Chemical Releases.

**U.S. STATE REGULATORY INFORMATION:** The components of this gas mixture are covered under the following specific State regulations:

**Alaska - Designated Toxic and Hazardous Substances:** Ethanol.

**California - Permissible Exposure Limits for Chemical Contaminants:** Nitrogen, Ethanol.

**Florida - Substance List:** Oxygen, Ethanol.

**Illinois - Toxic Substance List:** Ethanol.

**Kansas - Section 302/313 List:** No.

**Massachusetts - Substance List:** Oxygen, Ethanol.

**Minnesota - List of Hazardous Substances:** Ethanol.

**Missouri - Employer Information/Toxic Substance List:** Ethanol.

**New Jersey - Right to Know Hazardous Substance List:** Oxygen, Nitrogen, Ethanol.

**North Dakota - List of Hazardous Chemicals, Reportable Quantities:** No.

**Pennsylvania - Hazardous Substance List:** Oxygen, Nitrogen, Ethanol.

**Rhode Island - Hazardous Substance List:** Oxygen, Nitrogen, Ethanol.

**Texas - Hazardous Substance List:** Ethanol.

**West Virginia - Hazardous Substance List:** Ethanol.

**Wisconsin - Toxic and Hazardous Substances:** Ethanol.

**CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):** No component of this gas mixture is on the California Proposition 65 lists. (Note: Only Ethyl Alcohol in alcoholic beverages is listed as a reproductive toxin).

### ADDITIONAL CANADIAN REGULATIONS:

**CANADIAN DSL/NDL INVENTORY STATUS:** The components of this gas mixture are listed on the DSL Inventory.

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:** The components of this gas mixture are not on the CEPA Priorities Substances Lists.

**CANADIAN WHMIS CLASSIFICATION:** This gas mixture is categorized as a Controlled Product, Hazard Class A, as per the Controlled Product Regulations.

## 16. OTHER INFORMATION

### INFORMATION ABOUT DOT-39 NRC (Non-Refillable Cylinder) PRODUCTS

DOT 39 cylinders ship as hazardous materials when full. Once the cylinders are relieved of pressure (empty) they are not considered hazardous material or waste. Residual gas in this type of cylinder is not an issue because toxic gas mixtures are prohibited. Calibration gas mixtures typically packaged in these cylinders are Nonflammable n.o.s., UN 1956. A small percentage of calibration gases packaged in DOT 39 cylinders are flammable or oxidizing gas mixtures.

For disposal of used DOT-39 cylinders, it is acceptable to place them in a landfill if local laws permit. Their disposal is no different than that employed with other DOT containers such as spray paint cans, household aerosols, or disposable cylinders of propane (for camping, torch etc.). When feasible, we recommended recycling for scrap metal content. CALGAZ will do this for any customer that wishes to return cylinders to us prepaid. All that is required is a phone call to make arrangements so we may anticipate arrival. Scrapping cylinders involves some preparation before the metal dealer may accept them. We perform this operation as a service to valued customers who want to participate.

**MIXTURES:** When two or more gases or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

Further information about the handling of compressed gases can be found in the following pamphlets published by: Compressed Gas Association Inc. (CGA), 1725 Jefferson Davis Highway, Suite 1004, Arlington, VA 22202-4102. Telephone: (703) 412-0900.

P-1 "Safe Handling of Compressed Gases in Containers"

AV-1 "Safe Handling and Storage of Compressed Gases"

"Handbook of Compressed Gases"

### PREPARED BY:

CHEMICAL SAFETY ASSOCIATES, Inc.

PO Box 3519, La Mesa, CA 91944-3519

619/670-0609

Fax on Demand: 1-800/231-1366



**AIR LIQUIDE**

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this gas mixture. To the best of CALGAZ knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.